



# Centrifugal Pump

RESISTANT

# NON CLOG VERTICAL SUBMERSIBLE PUMP

### Contact Us



+91-44-4301 2183 / +91-7200627289

0

sales@neweraengineers.com

No.96-A, TTK Road,, Alwarpet, Chennai, Tamil Nadu 600018, INDIA.

## NON CLOG VERTICAL SUBMERSIBLE PUMP

These pumps are suitable for pumping soiled & wastewater. With their 50 mm solid handling capacity, they are able to pump liquids with larger suspended solids like fibres, textiles, etc. They are used for various applications in the public sector, private sector and trade industries.





#### Features

- Float Switch Internal or External can be provided for dry running protection
- Impeller Design Channel, Vortex, Cutter and Grinder
- Non Clog

#### M.O.C

- CI
- 55304
- **SS316**

### About Pump

- Flow Range Max 1800 Lpm
- Frequency 50 Hz

**Specifications** 

- Liquid Temp.- Max 40 Deg C
- 🗕 Max. Head Max 36 mwc
- Solid Passage Spherical 50 mm

#### Applications

- Buildings
- Effluent Treatment Plants
- Ground Water Drainage
- Hospitals
- Industrial Wastewater
- Schools & Colleges
- Sewage Treatment Plants
- Submersible Cutter Sewage Pumps
- Wastewater Treatment System

